

SERIES 1800 DOUBLE HUNG

- **Series 1800 2- and 3-lite sliders and picture windows are available**
- Exclusive InsulKor™ polyurethane fiberglass-enriched sash reinforcement for superior thermal and structural performance
- ¾" constant force coil balance offers incredibly easy sash mobility
- Fusion-welded sashes and frame add strength and boost insulation
- Low-E glass with insulating argon gas yields outstanding thermal efficiency
- DP 60 rating (window size tested 36" x 74")
- Beveled mainframe offers a stylish exterior appearance
- Dual push-button night latches position sashes for optimal ventilation

- Integrated slim-line lift rail allows you to easily operate sash
- 4 ¼" frame thickness enhances appearance as well as structural integrity
- External accessory groove accommodates nail fin option
- Full screen is standard and removable from the inside*
- Dual low profile, positive-action cam locks increase security (2 locks standard at 27 ¼" width or wider)
- Full interlocking lock and meeting rail
- Full vinyl sash dam on sill and high-performance weather stripping protect against air infiltration
- 3.25" jamb depth for ideal window sizing
- **Transferable limited lifetime warranty**
- **Lifetime glass breakage warranty**



CUSTOM Options

- **Low-E Glass**
- **Ultra Low-E Glass with Argon Gas** (May be required for Energy Star rating.)
- Triple-pane, R-5 compliant glass panels
- Super Spacer® nXt™ sealant system for optimal thermal performance (standard with triple-pane option)
- InsulKor™ multi-cavity foam-filled frame

- Exclusive locking half screen*
- Nail fin accessory for use in remodeling or new construction applications
- 1 ½" simulated divided lite (SDL) grid
- ⅝" or 1" contoured, ⅝" or ¾" flat, ⅝" contoured valance grids
- Obscure or double-strength glass



SCAN AND WATCH A VIDEO ABOUT OUR SERIES 1800

InsulKor™ Technology




COLOR Options**



Color options available in 1800, casements, awnings, sliders, bays and bows.

LOCK Options**



All products may be ordered to meet Energy Star requirements.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.
 *Screens are not meant to restrain a child from falling through an open window.
 **Printing process may affect color shown. Please refer to actual window sample when selecting colors.
 ***Grid offering limited to ⅝" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.

SCAN AND EXPERIENCE OUR WEBSITE

